



SPC-1709

17" Intel® Atom™ SoC Processor E3845 Fanless
Stainless Steel Chassis Touch Panel PC with Full
IP-65

- > Fanless Onboard Intel® E3845 / J1900 processor with Integrated Chipset
- > One 204-pin DDR3L SODIMM Socket Supports Up to 8GB DDR3L 1333 SDRAM
- > 3 USB, 1 LAN, 1 COM
- > Wide Voltage +12V ~ +26V Input, ErP Power
- > Full System IP65

+ Spec

System Information

Processor	Intel® Atom™ E3845 4-Core 1.91GHz processor/ Intel® Celeron® J1900 2.00GHz processor
System Memory	1 x 204-Pin DDR3L 1333MHz SO-DIMM up to 8 GB
I/O Chipset	EC ITE IT8528E
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./Monitoring CPU & System Temperature and Voltage 1sec.step
H/W Status Monitor	Monitoring CPU & System Temperature and Voltage
SBC	EBM-BYT

Expansion

Expansion	1 x Mini PCIe Support mSATA 1 x Mini PCIe Supports SIM Card
------------------	--

Storage

Storage	1 x CompactFlash Type VII Socket 1 x 2.5" Drive Bay
----------------	--

Panel

LCD Size	17", 4:3
Display Type	SXGA
Resolution	1280x1024
Pixel pitch	0.264mm(H) x 0.264mm(V)
Luminance	350 cd/m2
Contrast ratio	800
Viewing angle	80 (U), 80 (D), 85 (L), 85 (R)
Response time	30 ms
Backlight	LED
Touch Type	5 Wires resistive
Touch Light Transmission	80 %
Touch Controller	Onboard USB touch (EETI)

I/O

USB Port	3 x waterproof USB 2.0
COM Port	1 x waterproof DB9
SATA	1 x SATA II

Wireless Communication

WLAN	Optional WIFI Module 802.11 ac/a/b/g/n/
-------------	---

Display

Graphic Chipset	Intel® Valleyview SoC integrated Graphics Supports dual display
Spec. & Resolution	HDMI:Max. resolution 1920x1200@ 60Hz

Audio

Audio Codec	Realtek ALC888S
Audio Interface	Line-Out
Speaker Output	2 x 5W (Optional)

Certifications

Certification Information	CE / FCC Class A
----------------------------------	------------------

Ethernet

LAN Chipset	1 x Intel® I210IT
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	1 x waterproof LAN

Power Requirement

DC Input	+12V ~ +26V
DC Input Connector	Waterproof Lockable DC Jack



Power Mode	AT/ATX (ATX is default setting)
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter AC-DC Adapter
Mechanical & Environmental	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H)	405 x 353 x 66.6mm
Weight	7.5Kgs
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan	Fanless
Construction - Front	Front & Rear Silver Stainless
Construction - Rear	Black
Software Support	
OS Information	Win 7 Win 8 Linux
Ordering Information	
Ordering Information	SPC-1709-190-A4R Intel Celeron SoC J1900 2.0GHz D1-CPU/4G DDR3L/32G SSD/1GLAN/COM/3USB/12~26V input/24V Adapter SPC-1709-384-A4R Intel E3845 D1-CPU/4G DDR3L/32G SSD/1GLAN/1COM/3USB/12~26V input/24V Adapter ACC-ARM-D1R VESA STAND, 75mm & 100 mm ACC-ARM-D23R VESA STAND, 75mm & 100 mm ACC-SPC-WIFI-1R Wifi Kits for SPC-15/17/22 802.11b/g/n MPCle/2Antenna/Cable