

UPower Lite-62

6-slot charger



Features

- Battery information monitor remotely (ORION)
- Capable of charging 6 batteries simultaneously
- 6 Independent LED indicators, clearly reveal recharge status
- High-speed recharge and over charge protection

Specifications

Main Specifications

Battery Charge Time	2.5 hrs for 85%, 3.5 hrs for 100%
Input Power	24V/250W adapter
Protection	Supports protection from over-voltage (input), over-current (input and output), short circuit, over-charge.
IO Interface	USB TypeA x 1(Data transport only), DC-in x 1
Certification	CE, FCC

Mechanical and Environmental

Architecture	ABS + PC
Color	White
Dimension	304(L) x 154(W) x 41(H) mm
Net Weight	1.16kg (2.56 lbs)
Packing Size	470(L) x 380(W) x 100(H) mm
Gross Weight	3kg (6.61 lbs)
Operating Temperature	0°C ~ 40°C(32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C(-4°F ~ 140°F)
Storage Humidity	10%~95%@35°C, non-condensing

Battery LED Indicator

Blue Lighting	Full Charge (AC mode)
Blue Flashing	Charging (AC mode)
Green Lighting	N/A
Orange Lighting	N/A
Purple Lighting	N/A
Green-Purple Flashing	N/A

Power Supply Specification

Input Voltage	100-240V AC @50-60 Hz
Output Power	24V / 10.41A, 250W max

Battery Pack (optional)

Battery Type	6/9/12 Cell Lithium-ion battery
Battery Capacity	5700 / 8550 / 12060 mAh
Output Voltage	10.8 / 10.95 / 10.8V

Ordering Information

- » UP-L62-A1-1010
6-slot Charger + 24V/250W adaptor. USB.